



SulfurHound Lite

The SulfurHound Lite provides reliable, continuous H₂S monitoring with electrochemical detection, built for Division 2 and Zone 2 hazardous locations. With low maintenance and a compact design, it delivers high accuracy, making it ideal for gas processing, pipeline, and biogas applications.

Applications

- Gas Processing Facilities
- Natural Gas Pipeline
- Chemical Plants
- Gas Well Testing & Analysis
- Landfills
- Biogas




Benefits

- Precise H₂S Detection
- Hazardous Location Certified
- Low Maintenance
- Real-Time Continuous Monitoring
- User-Friendly Touchscreen Interface

Operational Impact

- Optimized process control
- Safe operation in Div 2/Zone 2
- Reduced downtime and costs
- Enhanced responsiveness
- Simplified operation



Scan to know
more about KECO
SulfurHound Lite



Specifications

RANGE

- 0-10, 0-50, 0-100, 0-200, 0-1000, & 0-2000 ppm by vol.

RESOLUTION

- <0.05 ppm for ranges up to 200 ppm
- <0.5 ppm for ranges above 200 ppm

REPEATABILITY

- ±3% of Full Scale

ACCURACY

- ±3% of Full Scale

OVERGAS LIMIT

- Maximum 500 ppm for ranges up to 200 ppm
- Maximum 10,000 ppm for ranges above 200 ppm

TEMP PERFORMANCE

- ±10% of reading up to 50% full scale and
±15% of reading from 50% to 100% full scale

RESPONSE TIME

- T90 = less than 60 seconds

POWER

- 110/220VAC 50/60 Hz or 24VDC (1.1 amps max)

OUTPUT

- 4-20mA DC (self-powered)
- RS-485 Modbus
- TCP/IP Ethernet Modbus
- Concentration alarms via Modbus
- Diagnostic Alarms via Modbus

ELECTRICAL CLASS

- Class I, Div 2 (Zone 2) Groups B, C, D

HUMIDITY

- 15-90% RH non-condensing
*analyzer performance based on laboratory conditions

OPERATION TEMPERATURE

- -10°C to 50°C

OPERATION PRESSURE

- Max pressure input 100 psig (optional pressure regulator/gauge available)
- Minimum pressure input 10 psig

DIMENSIONS

- Height: 20 inches
- Width: 12 inches
- Depth: 7 inches

WEIGHT

- Approx. 40 lbs

FEATURES

- Data Logger (SD card separate)
- Enclosure for outdoor environments (UL listed, CSA rated, IP66)
- Sample flow rate is 1.5 SCFH on sample requirement

OPTIONS

- Alarm relays (SPDT, 250 VAC @ 5 Amps)
- Isolation of 4-20 mA and Ethernet
- Solar System (panels, mounting pole, batteries, controller)
- H2S Scrubber for vent
- Fugitive Emission Control Unit for vent
- Sampling System (Simple): Pressure regulator/gauge
- Sample System for Gasses Entrained with Light Liquids: Pressure regulator/gauge, Liquid Block, by-pass with needle valve
- Sampling System for LPG, LNG (heated)
- Sample Probe to be installed at tap point
- Self-standing rack (includes sun/rain shield, drip pan, fork lift holes, foundation mount holes; can mount analyzers on front and back)

KECO provides design and application engineering assistance for the User's analyzer requirements. For a quotation, please complete Analyzer Quote Request Form at kecosystems.com/quote

KECO reserves the right to make revisions and or changes without notice. KECO shall not be liable for any errors or omissions made or any damages resulting from the use of the analyzer, information, or the manual. © 2025 Printed in the USA.